UBX-T SERIES [SHUT-OFF TYPE]

Premium Type Battery Oil-Pulse Tool equipped with PHOENIX**Pulse Unit and Auto-Relief**



FEATURE

- Weight Reduced by 20% & Overall Length Downsized by 47mm (*Compared with UDBP-TA70(P))
- Newly developed diaphragm improves fastening accuracy by sensing inner pressure of the pulse unit precisely.
- Incomplete Job Error Detection function (TK) is standardized.
- Improvement of operator's visual confirmation by LED lamp for fastening judgement

Wireless RF8 Type / Z(ZigBee) Type (*)

*For information on the Radio Law in your country, please contact your nearest URYU distributor.

RF8 : Pokayoke configuration

Z(ZigBee) : Pokayoke configuration



Relay output exclusive cable assembly

Specifications (Shut-off Type)

Model	Capacity (Nominal Bolt Size)		Torque Range		Free Speed (Approx.)	Overall Length less Socket or Bit (Approx.)					From Center to Outside (Approx.)		Sq. Drive or Hex. Size		Battery Voltage (Capacity)	Battery Model (Panasonic)	Number of fastening per	Fastener quantity per full	Code	
	mm	in	Nm	ft-lbs	min⁻¹	mm	in			with no battery		mm in	mm	in	(σαμασιτή)	(i anasonic)	minute *	charge		
								kg	lb	kg	lb									
UBX-T70	8-12	5/16-1/2	25.0-55.0	18.5-40.7	4800	187	7 23/64	1.63	3.59	1.28	2.82	27.5 1 3	1 3/32	9.5	3/8	14.4V(2.0Ah)	EYFB41	8	250	12F02
								1.86	4.10	1.28	2.82	21.5	1 3/32	5.5	0,0	14.4V(4.2Ah)	EYFB42	Ŭ	600	
UBX-T70(RF8)	0 12	5/16 1/0	25 0 55 0	10 5 40 7	4800	193 7 1	7 19/32	1.63	3.59	1.28	2.82	27.5 1 3/32	1 3/32	9.5	3/8	14.4V(2.0Ah)	EYFB41	8	250	12F22
UDA-170(KF6)	0-12	5/10-1/2	25.0-55.0	10.3-40.7	4000		1 19/32	1.86	4.10	1.28	2.82	21.5	21.5 1 3/32			14.4V(4.2Ah)	EYFB42		600	121-22
UBX-T70(Z)	8-12	5/16-1/2	25.0-55.0	18.5-40.7	4800	204	8 1/32	1.63	3.59	1.28	2.82	27.5	1 3/32	9.5		14.4V(2.0Ah)	EYFB41	8	250	12F32
								1.86	4.10	1.28	2.82					14.4V(4.2Ah)	EYFB42		600	12532

*Torque Range is a guideline value. Please make tool selection appropriately in accordance with an actual application. *Battery or Battery Charger is not included. Please use EY0L82 (Panasonic) for Battery Charger *Calculated under URYU test condition. It varies depending on the usage condition.

OPTION

Optional Tool Jackets

•	
Part Number	Used for
12F-840-0	UBX-T70
12F-840-1	UBX-T70(RF8)
12F-840-3	UBX-T70(Z)

To UTM-1500 or PLC