

UBX-T SERIES [SHUT-OFF TYPE]

Premium Type Battery Oil-Pulse Tool with PHOENIX Pulse Unit and Auto-Relief



UBX-T60D



UBX-T70



UBX-T80

FEATURE

- Compact & Light weight, Low noise, Low vibration, Low reaction & Speedy fastening
- Shut-off reliability improved by diaphragm
- Incomplete Job Error Detection function (TK) is standardized.
- Double-hitting Detection: When a tool shuts off with 2 or less pulses, it is detected as the fastening NOK.

Specifications (Shut-off Type)

Model	Capacity (Nominal Bolt Size)		Torque Range		Free Speed (Approx.)	Overall Length less Socket (Approx.)		Weight less Socket				From Center to Outside (Approx.)		Sq. Drive or Hex. Size		Battery Voltage (Capacity)	Battery Model (Panasonic)	Number of fastening per minute *	Fastener quantity per full charge	Code
	mm	in	Nm	ft-lbs	min ⁻¹	mm	in	with battery		with no battery		mm	in	mm	in					
								kg	lb	kg	lb									
UBX-T40D	5-6	No.10-1/4	5-9	3.7-6.6	3000	183	7 13/64	1.54	3.39	1.25	2.75	27.5	1 3/32	6.35	1/4	10.8V(2.0Ah)	EYFB32	11	800	12C02
UBX-T50D	6-8	1/4-5/16	8-17	5.9-12.5	3900	183	7 13/64	1.54	3.39	1.25	2.75	27.5	1 3/32	6.35	1/4	10.8V(2.0Ah)	EYFB32	10	650	12D02
								1.60	3.52							14.4V(2.0Ah)	EYFB41		330	
UBX-T60D	8-10	5/16-3/8	15-30	11.1-22.1	4800	183	7 13/64	1.83	4.03	1.25	2.75	27.5	1 3/32	6.35	1/4	14.4V(4.0Ah)	EYFB43	8	750	12E02
								1.83	4.03							14.4V(4.2Ah)	EYFB42		790	
UBX-T50	6-8	1/4-5/16	9-20	6.6-14.8	3900	179	7 3/64	1.54	3.39	1.25	2.75	27.5	1 3/32	9.5	3/8	10.8V(2.0Ah)	EYFB32	10	750	12D12
								1.60	3.52							14.4V(2.0Ah)	EYFB41		330	
UBX-T60	8-10	5/16-3/8	18-36	13.3-26.6	4800	179	7 3/64	1.83	4.03	1.25	2.75	27.5	1 3/32	9.5	3/8	14.4V(4.0Ah)	EYFB43	8	750	12E12
								1.83	4.03							14.4V(4.2Ah)	EYFB42		790	
								1.63	3.59							14.4V(2.0Ah)	EYFB41		250	
UBX-T70	8-12	5/16-1/2	25.0-55.0	18.5-40.7	4800	187	7 23/64	1.86	4.10	1.28	2.82	27.5	1 3/32	9.5	3/8	14.4V(4.0Ah)	EYFB43	8	570	12F02
								1.86	4.10							14.4V(4.2Ah)	EYFB42		600	
UBX-T80	10-12	3/8-1/2	35.0-65.0	25.9-48.1	4800	193	7 19/32	1.89	4.16	1.40	3.08	27.5	1 3/32	9.5	3/8	18.0V(3.0Ah)	EY9L53	5	480	12F52

*Torque Range is a guideline value. Please make tool selection appropriately in accordance with an actual application.

*Battery or Battery Charger is not included. Please use EY0L82 (Panasonic) for Battery Charger.

*Calculated under URYU test condition. It varies depending on the usage condition.

OPTION

Optional Tool Jackets

Part Number	Used for
12E-840-1	UBX-T60(D)

Part Number	Used for
12F-840-0	UBX-T70

Part Number	Used for
12F-840-5	UBX-T80